CM/1
Conductivity meter
For measuring the conductivity level and the display for changing the cartridge.



- Suitable for full demineralisation cartridges
- Optical and acoustic display for cartridge change
- 10 switch points in measuring range 0 – 199.9 µS/cm
- One-line display, connection to external LED possible
- Including wall bracket and power unit

EAN: 4002516057420 / Material number: 10889920 /
Old Material Number: 69450002D

Product category	
Fresh-water dishwashers	•
Tank dishwashers	•
Throughfeed tank dishwashers	•
Laboratory glasswashers	•
Thermal disinfectors	•
Washer-disinfectors, medical	•
Machine affiliation	
G 8066	•
PG 8067	•
PG 8041	•
PG 8043	•
PG 8045	•
PG 8060	•
PG 8063	•
PG 8164	•
PG 8165	•
PG 8166	•
PG 8169	•
PTD 901	•
PFD 400	•
PFD 400 U	•
PFD 401	•
PFD 401 U	•
PFD 402	•
PFD 402 U	•
PFD 404	•
PFD 404 U	•
PFD 405	•
PFD 405 U	•
PFD 407	•
PFD 407 U	•
PTD 701	•
PTD 702	•
PTD 703	•
PTD 704	•
PG 8581	•
PG 8582	•
PG 8583	•
PG 8583 CD	•
PG 8591	•
PG 8592	•
PG 8593	•
Product category	
Water treatment	•
Product characteristics	
Material	Plastic
Color	Black

CM/1
Conductivity meter
For measuring the conductivity level and the display for changing the cartridge.



EAN: 4002516057420 / Material number: 10889920 /
Old Material Number: 69450002D

Dimensions and weight	
External dimensions, net height in inches	4 3/8 (110)
External dimensions, net width in inches	4 15/16 (125)
External dimensions, net depth in inches	2 1/16 (52)
External dimensions, gross height in inches	6 1/8 (155)
External dimensions, gross width in inches	12 1/4 (310)
External dimensions, gross depth in inches	13 13/16 (350)
Net weight in lbs	3 (1.56)
Gross weight in lbs	5 (2.16)