Miele

# PDR 908 [EL]

Professional vented dryer, Little Giants, electrically heated
with extremely short program runtimes. Performance 18 (8.0) lb (kg) in 62 min.




- Drum volume 4.59 (130.00) ft³ (l), load size 18 (8.0) lb (kg)
- Tested for intensive use – unique Miele quality
- Top convenience with full-touch color display – M Touch Flex
- Precision drying of all fabrics – PerfectDry
- Future-proof connectivity via Wi-Fi

EAN: 4002516195573 / Material number: 11204500 /
Old Material Number: 52908359NAM

| | |
|---|---|
| **Construction type and design** | |
| Design | Front loader, stackable |
| Linie | Performance Plus |
| Front | Lotus White |
| Side panels | Powder-coated, lotus white |
| Control panel color | Stainless Steel |
| Load in lbs.(kg) | 18 (8.0) |
| Drum volume in ft³ (l) | 4.59 (130.00) |
| Drying system | Exhaust air |
| Door opening [Ø] in in.(mm) | 14 5/8 (370) |
| Door opening angle in degrees | 167 |
| Door hinging | left |
| Stainless steel honeycomb drum | Yes |
| **Application** | |
| Suitable for the hotel and catering industry | • |
| Suitable for retirement and care homes | • |
| Suitable for facility management | • |
| Suitable for dry cleaners | • |
| Suitable for commercial laundries | • |
| Suitable for small businesses | • |
| Suitable for universities, nurseries, and schools | • |
| Suitable for hospitals | • |
| Suitable for sports clubs | • |
| Suitable for beauty salons, spas and fit ness centers | • |
| Suitable for doctors' and dentists' practices | • |
| Suitable for the petrochemical industry | • |
| Suitable for the food-processing industry | • |
| Suitable for amusement parks and holiday complexes | • |
| **Performance data** | |
| Maximum evaporation capacity in l/hour and gal. qts./hour | 0.9 (3.7) |
| Specific energy consumption in kWh/kg an d kWh/p | 0.49 |
| Specific energy consumption for cottons/Normal drying, residual moisture 48% in kWh/kg | 0.49 |
| Specific energy consumption for mixed fabric/Normal drying, residual moisture 40% in kWh/kg | 0.41 |
| Program cycle in min. | 62 |
| Program cycle time for cottons/Normal drying, residual moisture 48% in min. | 62 |
| Program cycle time for cottons/Normal drying, residual moisture 40% in min. | 57 |
| **Control** | |
| Control system | M Touch Flex |
| Programmability | programmable |
| Program controls | Residual moisture controlled |
| Max. delay start in h | 24 |
| Countdown indicator | • |
| Program sequence indicator | • |
| Language can be selected easily at any time | • |

PDR 908 [EL]

Professional vented dryer, Little Giants, electrically heated
with extremely short program runtimes. Performance 18 (8.0) lb (kg) in 62 min.




EAN: 4002516195573 / Material number: 11204500 /
Old Material Number: 52908359NAM

| | |
|---|---|
| **Standard electrical connection** | |
| Type of heating | Electric |
| Electrical connection | 2~208-240V 60HZ |
| Electric heater rating in kW | 3.03 - 4.04 |
| Total connected load in kW | 3.40 - 4.30 |
| Fuse rating in A | 30 |
| NEMA plug: Twist Lock L6-30 | • |
| **Dimensions and weight of dryer** | |
| External dimensions, net height in inches | 33 1/2 (850) |
| External dimensions, net width in inches | 23 1/2 (596) |
| External dimensions, net depth in inches | 28 1/4 (717) |
| External dimensions, gross height in inches | 37 1/16 (940) |
| External dimensions, gross width in inches | 26 (660) |
| External dimensions, gross depth in inches | 32 5/16 (820) |
| Net weight in lbs. (kg) | 120 (54.0) |
| Gross weight in lbs. (kg) | 133 (60) |
| Maximum floor load in N | 920 |
| **Emission values** | |
| Emissions – sound pressure at workplace | ≤70 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h | 0.76 |
| **Features** | |
| Intelligent drum reversal | • |
| Axial airflow | • |
| Large-surface filter | • |
| PerfectDry | • |
| SoftLift drum ribs | • |
| Low temperature function | • |
| Communication slot | • |
| Drying basket (optional) | • |
| Drum lighting | • |
| Machine-independent accessories | • |
| **Efficiency** | |
| Recycling rate in % | 95 |
| **Connection options** | |
| Optical interface for service access | • |
| Peak-load negotiation / energy management (optional) | • |
| WiFiConn@ct | • |
| **Standards, test certificates, and symbols** | |
| WEEE | • |
| c ETL US | • |