PFD 408 U [208V]

Built-under fresh water dishwasher

ADA compliant, NSF/ANSI 3 certified for sanitization. Industrial use only.



- Max. cleaning performance*: 152 plates/h
- First-class results thanks to fresh water system
- Extremely hygienic results – final rinse temperature of 185 (85) °F (°C)
- Safe and easy operation – automatic door opening
- Flexible processing of two wire or plastic baskets per cycle

* Program runtime without drying. The values quoted may vary depending on the on-site conditions (water intake temperature/electrical connection).

EAN: 4002516577355 / Material number: 12066580 /
Old Material Number: 61040830NAM

Construction type and design	
Model	Built-under dishwasher
Range	MasterLine
Model	HygienePro
Wash system	Fresh water front loader
Number of levels	2
Front	Stainless steel
Lid	Without lid
Side walls	Galvanised
Application	
Suitable for retirement and care homes	•
Suitable for small restaurants/bars	•
Suitable for hospitality industry	•
Suitable for Bed & Breakfast	•
Suitable for canteens	•
Suitable for child care facilities	•
Suitable for fast food restaurants	•
Performance data	
Certified hygiene	•
Shortest program duration in min.	15
Maximum final rinse temperature in °F (°C)	185 (85)
Cleaning performance, plates/h	152
Cleaning performance, baskets/h	8
Possible to wash plastic baskets on two levels	•
Service life in wash cycles	28000
Control	
Control system	M Touch Flex
Max. delay start in h	24
Countdown indicator	•
Dishwashing programs [number]	4
Adjustable temperature holding time	•
Adjustable final rinse temperature	•
Program sequence indicator	•
Choice of display language	•
Language-neutral operation	•
Standard electrical connection	
Electrical connection	3 AC 208V 60HZ
Heater rating in kW	5.40
Total connected load in kW	5.80
Fuse rating in A	20
Length of power cord in ft (m)	6 (1.90)
NEMA plug: Twist Lock L15-20	•
Possible voltage variant 1	
Electrical connection	2 AC 208V 60HZ
Heater rating in kW	5.40
Total connected load in kW	5.80
Fuse rating in A	30

PFD 408 U [208V]
Built-under fresh water dishwasher
ADA compliant, NSF/ANSI 3 certified for sanitization. Industrial use only.



EAN: 4002516577355 / Material number: 12066580 /
Old Material Number: 61040830NAM

Water connection/drainage	
Cold water [number]	1
Hot water [number]	1
Required flow pressure in bar	1.00 - 10.00
Drain hose [DN]	22
Maximum delivery head for drain pump in inches (cm)	39 3/8 (100)
Integrated water softener	•
Maximum water hardness in gpg (mmol/l)	62.59 (10.70)
Water protection system	Waterproof system
Water consumption per wash cycle in gal (l)	4.6 (17.50) gll (l)
Length of water inlet hose in inches (cm)	67 (170)
Length of water drain hose in inches (cm)	59 1/8 (150)
Dimensions and weight	
External dimensions, net height in inches	32 5/16 (820)
Maximum height adjustment in inches (mm)	60.00
External dimensions, net width in inches	23 9/16 (598)
External dimensions, net depth in inches	23 7/16 (595)
External dimensions, gross height in inches	36 1/4 (920)
External dimensions, gross width in inches	26 7/16 (670)
External dimensions, gross depth in inches	29 3/16 (740)
Usable space in wash cabinet, width in inches (mm)	22 1/16 (559)
Usable space in wash cabinet, height in inches (mm)	21 1/8 (536)
Usable space in wash cabinet, depth of upper basket in inches (mm)	18 11/16 (474)
Usable space in wash cabinet, depth of lower basket in inches (mm)	20 3/8 (516)
In-feed height above floor in inches (mm)	8 9/16 (216)
Required niche width in mm	23 5/8 (600)
Net weight [kg]	166 (75)
Gross weight in lbs.	188 (85)
Maximum floor load in N/m^2	1200
Emission values	
Emission sound pressure level in workplace (LpA)	45 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	57.0
Heat dissipation into the room in MJ/h	1.44
Programs	
Normal Plus	•
Normal	•
Cold/Pre-wash	•
Intensive	•
Reactivation	•
Drainage by pump	•
Baskets	
MasterLine baskets	•
Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•
Features	
Drying	AutoOpen assisted drying
AutoClose	•

PFD 408 U [208V]
Built-under fresh water dishwasher
ADA compliant, NSF/ANSI 3 certified for sanitization. Industrial use only.



EAN: 4002516577355 / Material number: 12066580 /
Old Material Number: 61040830NAM

1 Combi dispenser/door for powder and liquid media	•
In-door salt container	•
Door lock, code-protected if required	•
Safe mode	•
Highly effective filter system with filter monitoring	•
Aerosol steam condenser	•
Wash cabinet made from high-quality stainless steel	•
Optical interface	•
A wide range of accessories (optional)	•
Connection options	
External dispenser module for liquid cleaning agent	•
Wi-Fi	•
Standards, test certificates, and symbols	
Splash protection IPX1	•
EMC radio suppressed	•
DIN 10512	•
DIN EN 17735	•
ETL	•
NSF	•
ADA compliant	•